



Kunde: *Fastvoice*
 Hersteller: *Carus*
 Artikelnummer: *Dim by Click*
 Verbrauch:
 Powerfaktor:

Results

| CIE 1931 2° observer | |
|----------------------|---------------------|
| x | 0.4608 |
| y | 0.4092 |
| u' | 0.2637 |
| v' | 0.5270 |
| L | 70.12 |
| a | 14.99 |
| b | 47.18 |
| X | 267.83 |
| Y | 237.84 Lumen |
| Z | 75.53 |

| Other | |
|--------------------|--------------------|
| CCT | 2676 Kelvin |
| Chromaticity Error | 0.002 |
| Color Peak | 623.55 |
| Color Peak Value | 5.25 |
| Color Dominant | 584.5 |
| Luminous Intensity | |
| Purity | 0.612 |
| Radiometric | 852.67 |
| PAR | |
| PPFD | |

| Rendering Indices | |
|-------------------|-------------|
| Ra | 92.4 |
| R1 | 92.5 |
| R2 | 96.5 |
| R3 | 98.5 |
| R4 | 91.9 |
| R5 | 92.2 |
| R6 | 96.0 |
| R7 | 91.1 |
| R8 | 80.4 |
| R9 | 58.0 |
| R10 | 90.8 |
| R11 | 92.4 |
| R12 | 84.5 |
| R13 | 93.6 |
| R14 | 98.6 |

| Binning | |
|------------|-------|
| Binning | 2700K |
| Brightness | |

| Metamerism Indices | |
|--------------------|-----|
| Mivis | 2.8 |
| Miuv | 3.8 |

CIE 1931

